

Road Runner Plus

Diesel Fuel Improver with Biocide



Improves fuel efficiency and extends engine life.

- ◀ Reduces engine wear
- ◀ Boosts cetane rating by up to 15%, improving fuel efficiency
- ◀ Reduces exhaust emissions (HC, NO_x, CO, PMI)
- ◀ Provides clean separation of fuel and water – helps prevent contamination, rust and corrosion
- ◀ Lowers pour point; improves cold-weather starting
- ◀ Keeps combustion chamber, piston rings and injector tips clean
- ◀ Not classified as a Dangerous Good for transport or storage

FEATURES AND BENEFITS

Low-Sulphur Fuel Lubricity Enhancer

Contains LU-2000, and organically polar lubricity additive that plates metal surfaces and protects against wear.

Special Cetane Booster Improves Mileage

Increased cetane improves ignition, combustion, and fuel economy. Faster starts also help extend battery and starter life.

Demulsifiers Improve Engine Performance

Separate water from the fuel and prevent fuel contamination.

Keeps Injector Tips Clean

Helps keep fuel injector tips free from clogs by dispersing sludge and gum in fuel. Clean tips improve combustion and maximise performance.

Reduces Change-Outs of Filters

Biocide helps prevent formation of slime and blockages due to biological contamination.

Improves Fuel Quality

Helps prevent fuel breakdown and acid formation in stored fuel.



Road Runner Plus

Diesel Fuel Improver with Biocide



Improves fuel efficiency and extends engine life.

Areas of Application

Easy-to-Use Directions

- Trucking firms
- Delivery fleets
- Construction equipment
- Utility, mining and marine operations
- Stationary and auxiliary power engines
- Off-road vehicles
- Council maintenance departments
- Bus companies

For diesel engines only.

Do not use in petrol engines.

Bulk Storage Tanks: Add 1L for each 1,000L of diesel fuel

Vehicle Fuel Tanks: Add 1L for every 800L of diesel fuel

Technical Specifications

Flash Point	63°C
H ₂ O Solubility	Negligible
API Gravity	19.6 – 20.6
Meets or Exceeds	L-10 Cummins injector cleanliness specification

For low-cetane fuel, or fuel that gives poor cranking, the amount should be doubled.

Notice: Consult the label for full instructions and precautions before using the product.



MANTEK
Division of NCH Australia PTY LTD
A.B.N. 19 000 609 316
PO Box 6058 Alexandria NSW 2015
Toll Free: 1800 656 339



AS/NZS ISO 9001:2000